

Conformity certificate

Date: 21-08-2019

We hereby attest that following products are made of materials intended for food contact.

Product made of: Plastic

Products are listed on next page

- ➤ These products are in compliance with European regulation EC/1935/2004 of October the 27th and European regulation EC/2023/2006 of December the 22th
- ➤ These products are in compliance with regulation No 10/2011/EC for plastic materials and articles intended to come into contact with food
- ➤ These products are in compliance with Danish law BEK 1248 of October 30th, 2018.

Should you have any questions, do not hesitate to contact us.

ROSENDAHL DESIGN GROUP A/S

Slotsmarken 1
DK-2970 Hørsholm

Jegar Farmer hrestoff

Signed by:

Rosendahl Design Group - Slotsmarken 1 - DK-2970 Hørsholm

Version 8 – Gyldig fra: 04.02.2019 Dato: 04.02.2019 Godkendt af: JFC



Product number	Product name	Photo
36300	GC Lid for large oven-proof dish (25603)	
36301	GC Lid for medium oven-proof dish (25602)	
36302	GC Lid for small oven-proof dish (25601)	
36303	GC Lid for oven-proof bowl (25606)	
36304	GC Lid for oven-proof bowl (25605)	
36305	GC Lid for small oven-proof dish grey	
36306	GC Lid for large oven-proof dish grey	

Rosendahl Design Group - Slotsmarken 1 - DK-2970 Hørsholm



Product number	Product name	Photo
36307	GC Lid for medium oven-proof dish grey	
36308	GC Lid for round oven-proof bowl large, grey	
36309	GC Lid for round oven-proof bowl small, grey	



Draduct information:	Yes	No	Domonico
Product information:	165	No	Remarks
The Product can be used for all types of		X	
food and all types of process conditions (under normal and foreseeable condition of		^	
use):			
use).			
Suitable for:			If limit (to be mentioned)
Aqueous food			
	X		
Acidic foods			
	X		
Alcoholic foods			
	Χ		
Fatty foods			
	Х		
Dry foods	\ \ \		
The	X	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
The oven		X	
The microwave:		Х	
The Dishwasher:			At max 55°C
THE DISTIWASHEL.	X		At max 33 C
Other	, A	Χ	
Test/material/temperature:			
Total migration test performed			
	X		
Specific migration tests performed			
	X		
Dual use additives		Х	
Functional barrier		Х	
Temperature stable at max and min temperature:	-25°C	C - 55°	C

Dato: 04.02.2019 Godkendt af: JFC