

Declaration of Conformity

Date: 01-02-2023

We hereby attest that following products are made of materials intended for food contact.


<b>Products made of</b>	
Stainless Steel	X
Glass	X
Ceramic	X
Plastics	X

Products are listed on next page.

- These products are in compliance with European regulation EC/1935/2004 of October the 27th and European regulation EC/2023/2006 of December the 22th
- These products are in compliance with regulation No 10/2011/EC for plastic materials and articles intended to come into contact with food (if made of plastic)
- These products are in compliance with Danish law BEK 681 of May 25th, 2020.
- These products are in compliance with the Norwegian regulation FOR 1993-12-21 no. 1381.(if made of glass, ceramics and porcelain).

Should you have any questions, do not hesitate to contact us.

Signed by:



ROSENDAHL DESIGN GROUP A/S  
Slotsmarken 1  
DK-2970 Hørsholm

Rosendahl Design Group - Slotsmarken 1 - DK-2970 Hørsholm



ROSENDAHL  
DESIGN GROUP

Product number	Product name	Photo
15753	GC Nouveau Grinder H17 smoke	
20405	GC Nouveau Grinder H17 cm smoke 2 pcs.	
15754	GC Nouveau Grinder H17 blush	
20407	GC Nouveau Grinder H17 aqua	

Rosendahl Design Group - Slotsmarken 1 - DK-2970 Hørsholm



ROSENDAHL  
DESIGN GROUP

<b>Product information:</b>	<b>Yes</b>	<b>No</b>	<b>Remarks</b>
The Product can be used for all types of food and all types of process conditions (under normal and foreseeable condition of use):		X	
<b>Suitable for:</b>			If limit (to be mentioned)
Aqueous food		X	
Acidic foods		X	
Alcoholic foods		X	
Fatty foods		X	
Dry foods	X		
The oven		X	
The microwave		X	
The Dishwasher	X		<b>Only glass part.</b> Dishwasher safe, max 55°C
Other		X	
<b>Test/material/temperature:</b>			
Total migration test performed	X		
Specific migration tests performed	X		Plastic according to EU 10/2011/EC Glass and ceramic parts: Lead, cadmium and barium in compliance with the Norwegian limit.
Dual use additives(plastic)	X		No restriction (SML) according to 10/2011/EC
Functional barrier (Plastic)		X	
<b>Temperature stable at max and min temperature:</b>	0 - 40°C		